

## **CURVE/SPOT LIGHT/DEEP/FIXED**

**Model: RR-DL3308**



### **Feature:**

- Deep recessed
- Compact design
- High quality PMMA lens in different beam angles

### **Technical data:**

▪ Light source	COB Chip, Citizen or others
▪ LED Power (max.)	12.6W (350mA @36V)
▪ System Power (ref.)	15W (ref. only depends on the ECG)
▪ Lumen flux (typ.)	1000lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3 MacAdam
▪ Beam Angle	15D, 24D, 60D PMMA lens
▪ Tilttable	No
▪ Ingress protection	IP20
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Lifetime	50,000h L70B10
▪ Finishing	White RAL9016/Black RAL9005
▪ Construction	Aluminum, Polycarbonate
▪ Installation	Ceiling Recessed, spring type
▪ Dimension	90mm(OD)x73mm(H)/ cutout 82mm
▪ LED Driver	Remote
▪ Trimless version	No

### **Electronic control gear**

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI


**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

**\*\*Accessories: Honey comb\*\***

**\*\*The specification is subject to change without note.\*\***



↪ Cutout:82 mm

▨ 5-25mm