


ROUND DEEP/SPOT LIGHT/FIXED

Model: RR-DL3299



👁️ Cutout: 82mm

📏 5-25mm

Feature:

- Deep recessed
- Compact design
- High quality PMMA lens in different beam angles

Technical data:

- Light source COB Chip, Cree or others
- LED Power (max) 12.6W (350mA, 36V)
- System Power (ref.) 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 1050lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam step 3
- Beam Angle 24D, 36D, 45D PMMA lens
- Tiltable No
- Ingress protection IP44
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White RAL9016/Black RAL9005
- Construction Aluminum, Polycarbonate
- Installation Ceiling Recessed, spring type
- Dimension 90mm(OD)x73mm(H)/Cutout 82mm
- LED Driver Remote
- Trimless Version No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 3000K

medium 28°

wide 56°

h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1807	ø0.50	1	1353	ø1.06
2	451.7	ø1.00	2	338.2	ø2.13
3	200.8	ø1.51	3	150.3	ø3.20
4	112.9	ø2.01	4	84.55	ø4.27
5	72.27	ø2.51	5	54.11	ø5.33

****The specification is subject to change without note.****