


## DOUBLE REFLECT/SPOT LIGHT/TILTABLE

**Model: RR-DL3249**



☞ Cutout: 50mm

≡ 5-25mm



### Feature:

- Adjustable spot with mirror reflector
- Compact Design
- Low UGR

### Technical data:

- Light source COB or others
- LED Power (max) 5.4W (150mA, 36V)
- System Power (ref.) 7W (ref. only depends on the ECG)
- Lumen flux (typ.) 350lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra $\geq$ 90
- MacAdam Step 3
- Beam Angle 22D, 40D PMMA Lens
- Tiltable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Baffle Finishing Plain White/Plain Black/ Chrome
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 57.5mm(OD)x60mm(H)/Cutout 50mm
- LED Driver Remote
- Trimless version No

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

### Light Distribution For 2700K wide 40°

h(m)	E(lx)	∅(m)
1	515.6	∅0.57
2	128.9	∅1.14
3	57.29	∅1.71
4	32.22	∅2.28
5	20.62	∅2.85

**\*\*The specification is subject to change without note.\*\***