


BLACK HOLE/SPOT LIGHT/FIXED

Model: RR-DL3061



↻ Cutout: 65mm

≡ 5-25mm

Feature:

- Compact size
- Simple
- Low UGR

Technical data:

▪ Light source	COB or others
▪ LED Power (max)	9W (250mA, 36V)
▪ System Power (ref.)	11W <small>(ref. only depends on the ECG)</small>
▪ Lumen flux (typ.)	800lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3
▪ Beam Angle	20D, 36D, 50D PMMA Lens
▪ Tilttable	Yes
▪ Ingress protection	IP54
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Life time	50,000h L70B10
▪ Finishing	White/Black
▪ Baffle finishing	Black
▪ Construction	Aluminum
▪ Installation	Ceiling Recessed, Spring type
▪ Dimension	75mm(OD)x53mm(H)/Cutout 65mm
▪ LED Driver	Remote
▪ Trimless version	No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

****The specification is subject to change without note.****