

## SIMPLE/SPOT LIGHT/GIMBLE

**Model: RR-DL3090**



### Feature:

- Compact size
- Gimble tilt 25 degree
- Low UGR

### Technical data:

- |                          |                                   |
|--------------------------|-----------------------------------|
| ▪ Light source           | COB or others                     |
| ▪ LED Power (max)        | 7.2W (200mA, 36V)                 |
| ▪ System Power (ref.)    | 9W (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.)      | 600lm                             |
| ▪ Colour temperature     | 2700K, 3000K, 4000K               |
| ▪ Colour rendering index | Ra $\geq$ 90                      |
| ▪ MacAdam Step           | 3                                 |
| ▪ Beam Angle             | 24D, 36D, 45D PMMA Lens           |
| ▪ Tilttable              | Yes                               |
| ▪ Ingress protection     | IP21                              |
| ▪ Operation temperature  | 0-40C                             |
| ▪ Protection Class       | III                               |
| ▪ LED Life time          | 50,000h L70B10                    |
| ▪ Finishing              | White/Black                       |
| ▪ Construction           | Aluminum                          |
| ▪ Installation           | Ceiling Recessed, Spring type     |
| ▪ Dimension              | 93mm(OD)x43mm(H)/Cutout 83mm      |
| ▪ LED Driver             | Remote                            |
| ▪ Trimless version       | Yes, please contact us in detail  |

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI


**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

### Light Distribution For 2700K wide 46°

h(m)	E(lx)	ø(m)
1	971.4	ø0.85
2	242.8	ø1.70
3	107.9	ø2.55
4	60.71	ø3.40
5	38.85	ø4.25



➤ Cutout: 83mm

▨ 5-25mm

**\*\*The specification is subject to change without note.\*\***