


SQUARE/SPOT LIGHT/MEDIUM/BOX/SINGLE/TILTABLE

Model: SR-DL3232



▨ Cutout: 100x100mm

▨ 5-25mm

Feature:

- Single head square grilled downlight
- Gimble tilt 30 degree
- Compact design with IP54 rating

Technical data:

- Light source COB or others
- LED Power (max) 9W (250mA, 36V)
- System Power (ref.) 11W (ref. only depends on the ECG)
- Lumen flux (typ.) 650lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 110x110mmx52mm(H)/Cutout 100x100mm
- LED Driver Remote
- Trimless version Yes, please contact us in detail

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 2700K
wide 44.1°

h(m)	E(lx)	ø(m)
1	1235	ø0.81
2	308.7	ø1.62
3	137.2	ø2.43
4	77.17	ø3.24
5	49.39	ø4.05

****The specification is subject to change without notes.****