

FLOAT/SPOT LIGHT/FIXED/ROUND

Model: RR-DL3145



Feature:

- Compact recessed downlight
- Pendant effect
- Anti-glare

Technical data:

- Light source COB or others
- LED Power (max) 12.6W (350mA, 36V)
- System Power (ref.) 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 1200lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 15D, 24D, 60D PMMA Lens
- Tilttable No
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black/
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 100mm(OD) x 68mm(H)/Cutout 90mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



↻ Cutout: 90mm

≡ 5-25mm

Light Distribution For 2700K spot 15°

h(m)	E(lx)	ø(m)
1	1353	ø1.07
2	338.2	ø2.13
3	150.3	ø3.20
4	84.55	ø4.27
5	54.11	ø5.34

****The specification is subject to change without note.****