


## MINI CABINET/SPOT LIGHT/MINI DEEP/BLACK HOLED/FIXED/45mm

**Model: RR-DL3297**



↻ Cutout: 38mm

▨ 5-25mm

### Feature:

- MINI Deep with 5W LED power
- Small cutout 38mm
- Black hole

### Technical data:

- |                          |                                  |
|--------------------------|----------------------------------|
| ▪ Light source           | High Power LED                   |
| ▪ LED Power (max)        | 5.4W (150mA, 36V)                |
| ▪ System Power (ref.)    | 7 (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.)      | 250lm                            |
| ▪ Colour temperature     | 2700K, 3000K, 4000K              |
| ▪ Colour rendering index | Ra≥90                            |
| ▪ MacAdam Step           | 3                                |
| ▪ Beam Angle             | 20D, 36D, 50D PMMA Lens          |
| ▪ Tilttable              | No                               |
| ▪ Ingress protection     | IP21                             |
| ▪ Operation temperature  | 0-40C                            |
| ▪ Protection Class       | III                              |
| ▪ LED Life time          | 50,000h L70B10                   |
| ▪ Finishing              | White/Black                      |
| ▪ Construction           | Aluminum                         |
| ▪ Installation           | Ceiling Recessed, spring type    |
| ▪ Dimension              | 45mm(OD)x75mm(H)/Cutout 38mm     |
| ▪ LED Driver             | Remote                           |
| ▪ Trimless version       | No                               |

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

**\*\*The specification is subject to change without note.\*\***