


## SPOT/CYLINDAR/SLIM/RECESSED

**Model: RR-DL3639**



↻ Cutout: 55mm

≡ 5-25mm

### Feature:

- Recessed ultra slim cylinder spot light
- 355 degree rotate and 90 degree tilt
- Interchangeable baffle

### Technical data:

- |                          |   |
|--------------------------|---|
| ▪ Light source           | COB or others                                     |
| ▪ LED Power (max)        | 12.6W (350mA, 36V)                                |
| ▪ System Power (ref.)    | 15W <small>(ref. only depends on the ECG)</small> |
| ▪ Lumen flux (typ.)      | 900lm   |
| ▪ Colour temperature     | 2700K, 3000K, 4000K                               |
| ▪ Colour rendering index | Ra≥90   |
| ▪ MacAdam Step           | 3   |
| ▪ Beam Angle             | 20D, 36D, 50D                                     |
| ▪ Tilttable              | Yes   |
| ▪ Ingress protection     | IP21  |
| ▪ Operation temperature  | 0-40C   |
| ▪ Protection Class       | III   |
| ▪ LED Life time          | 50,000h L70B10                                    |
| ▪ Finishing              | White/Black                                       |
| ▪ Baffle Finishing       | White/Black/silver grey/brushed bronze            |
| ▪ Construction           | Aluminum  |
| ▪ Installation           | Ceiling Recessed, Spring type                     |
| ▪ Dimension              | 40mm(OD)x140mm(H)/Cutout 55mm                     |
| ▪ LED Driver             | Remote  |
| ▪ Trimless version       | No  |

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

**\*\*The specification is subject to change without note.\*\***