

TRACK/DOME GLASS SHIELD/ANTI-GLARE

Model: TRA-TR3040-1-48VDC



Feature:

- Dome shape glass shield
- 220Vac or 48D track build in track LED driver available

Technical data:

- | | |
|--------------------------|-----------------------------------|
| ▪ Light source | COB or others |
| ▪ LED Power (max) | 12.6W (350mA, 36V) |
| ▪ System Power (ref.) | NA (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.) | 900lm |
| ▪ Colour temperature | 2700K, 3000K, 4000K |
| ▪ Colour rendering index | Ra \geq 90 |
| ▪ MacAdam Step | 3 |
| ▪ Beam Angle | 24D, 36D, 60D Reflector |
| ▪ Tilttable | No |
| ▪ Ingress protection | IP21 |
| ▪ Operation temperature | 0-40C |
| ▪ Protection Class | III |
| ▪ LED Life time | 50,000h L70B10 |
| ▪ Finishing | White/Black |
| ▪ Construction | Aluminum |
| ▪ Installation | Track DC 48V |
| ▪ Dimension | 100mm(OD)x330mm(H) |
| ▪ LED Driver | Build in track LED driver |
| ▪ Trimless version | NA |

Electronic control gear

Build in track On/Off LED Driver
(Dimmable LED Driver is on request)

****The specification is subject to change without note.****

