

## TRIMLESS/SPOT LIGHT/GIMBLE/RECESSED/SQUARE TWIN HEADS Model: SR-DL3165



## Feature:

- Step in square trimless spot light .
- Low UGR
- Gimble tilt 25 degree

## **Technical data:**

<ul> <li>Light source</li> </ul>	COB or others
<ul> <li>LED Power (max)</li> </ul>	2x7.2W (200mA, 36V)
<ul> <li>System Power (ref.)</li> </ul>	2 x 9 W (ref. only depends on the ECG)
<ul> <li>Lumen flux (typ.)</li> </ul>	2x600lm
<ul> <li>Colour temperature</li> </ul>	2700К, 3000К, 4000К
<ul> <li>Colour rendering index</li> </ul>	Ra≥90
<ul> <li>MacAdam Step</li> </ul>	3
<ul> <li>Beam Angle</li> </ul>	24D,36D, 45D PMMA Lens
<ul> <li>Tiltable</li> </ul>	Yes
<ul> <li>Ingress protection</li> </ul>	IP21
<ul> <li>Operation temperature</li> </ul>	0-40C
<ul> <li>Protection Class</li> </ul>	III
<ul> <li>LED Lifetime</li> </ul>	50,000h L70B10
<ul> <li>Finishing</li> </ul>	White RAL9003/Black RAL9005
<ul> <li>Construction</li> </ul>	Aluminum
<ul> <li>Installation</li> </ul>	Trimless, Ceiling Recessed
<ul> <li>Dimension</li> </ul>	188x103mm/Cutout 190x105mm
LED Driver	Remote
Electronic control gear	
NON-DIM/Dimmable	INP MP series
1-10V/0-10V/DALI	SC series

55 63 145 188 ±25° 17 1

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Other brand is available upon request

istributio	n For 2700k
5°	
E(Ix)	ø(m)
1749	ø0.83
437.4	ø1.67
194.4	ø2.51
109.3	ø3.35
69.98	ø4.19
	E(lx) 1749 437.4 194.4 109.3



