


## DOUBLE REFLECT/SPOT LIGHT/TILTABLE

**Model: RR-DL3196**



⊕ Cutout: 82mm

⊕ 5-25mm



### Feature:

- Adjustable spot with mirror reflector
- Compact Design
- Low UGR

### Technical data:

- Light source COB or others
- LED Power (max) 12.6W (350mA, 36V)
- System Power (ref.) 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 800lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index  $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 17D, 24D, 36D Reflector
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Baffle Finishing Plain White/Plain Black/ Chrome
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 89mm(OD)x 120mm(H)/Cutout 82mm
- LED Driver Remote
- Trimless version Yes, please check with sale in detail

### Electronic control gear

NON-DIM/Dimmable

**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.

### Light Distribution For 3000K

medium 23.8°

wide 32.2°

h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	3772	ø0.42	1	2628	ø0.58
2	943.0	ø0.84	2	657.1	ø1.16
3	419.1	ø1.26	3	292.0	ø1.74
4	235.8	ø1.69	4	164.3	ø2.31
5	150.9	ø2.11	5	105.1	ø2.89

**\*\* Accessories (optional): Honeycomb Louvre, Diffuse glass (IP44)\*\***

**\*\*The specification is subject to change without note.\*\***