


BLACK HOLE/SPOT DOWNLIGHT/TILTABLE

Model: RR-DL3358



👁️ Cutout: 40mm

🔧 5-25mm

Feature:

- Compact size
- Black Ring
- Low UGR

Technical data:

▪ Light source	COB or others
▪ LED Power (max)	5.4W (150mA, 36V)
▪ System Power (ref.)	7W (ref. only depends on the ECG)
▪ Lumen flux (typ.)	500lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3
▪ Beam Angle	20D PMMA Lens
▪ Tiltable	Yes
▪ Ingress protection	IP21
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Life time	50,000h L70B10
▪ Finishing	White/Black
▪ Baffle Finishing	Black
▪ Construction	Aluminum
▪ Installation	Ceiling Recessed, Spring type
▪ Dimension	46mm(OD)x47mm(H)/Cutout 40mm
▪ LED Driver	Remote
▪ Trimless	No

Electronic control gear

NON-DIM/Dimmable

IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

Light Distribution For 2700K spot 20,4°

h(m)	E(lx)	ø(m)
1	1494	ø0.36
2	373.5	ø0.72
3	166.0	ø1.08
4	93.38	ø1.44
5	59.76	ø1.80

The specification is subject to change without note.