

SIMPLE/SPOT LIGHT/GIMBLE/ANTI-GLARE

Model: RR-DL3202



Feature:

- Compact size
- Gimble tilt 25 degree
- Low UGR

Technical data:

- Light source COB or others
- LED Power (max) 7.2W (200mA, 36V)
- System Power (ref.) 9W (ref. only depends on the ECG)
- Lumen flux (typ.) 600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, Spring type
- Dimension 92mm(OD)x62mm(H)/Cutout 83mm
- LED Driver Remote
- Trimless version No

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



➤ Cutout: 83mm

▨ 5-25mm

Light Distribution For 2700K wide 46°

h(m)	E(lx)	ø(m)
1	971.4	ø0.85
2	242.8	ø1.70
3	107.9	ø2.55
4	60.71	ø3.40
5	38.85	ø4.25

****The specification is subject to change without note.****