

SIMPLE/SPOT LIGHT/SQUARE/TWIN HEADS/GIMBLE

Model: RR-DL3167



Feature:

- Twin heads design
- Gimble tilt 25 degree
- Low UGR

Technical data:

- Light source COB or others
- LED Power (max) 7.2W x 2 (200mA x 2, 36V)
- System Power (ref.) 9Wx 2 (ref. only depends on the ECG)
- Lumen flux (typ.) 1200lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, Spring type
- Dimension 185x100mmx55mm(H)/Cutout 175x90mm
- LED Driver Remote
- Trimless version Yes, please contact us in detail

Electronic control gear

NON-DIM/Dimmable


IDP MP series

1-10V/0-10V/DALI

IDP SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.



Cutout: 175x90mm

5-25mm

Light Distribution For 2700K
wide 45°

h(m)	E(lx)	ø(m)
1	1749	ø0.83
2	437.4	ø1.67
3	194.4	ø2.51
4	109.3	ø3.35
5	69.98	ø4.19

****The specification is subject to change without note.****