

## SHOWER/SPOT LIGHT/FIXED/IP65/ HIGH POWER

**Model: RR-DL3043-15**



### Feature:

- Compact recessed downlight
- Interchangeable bezels
- IP65

### Technical data:

- Light source COB or others
- LED Power (max) 12.6W (350mA, 36V)
- System Power (ref.) 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 950lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index  $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 24D, 36D, 60D PMMA Lens
- Tilttable No
- Ingress protection IP65
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black/Chrome/Brushed  
Nickel/Brushed Brass
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 92mm(OD)x58mm(H)/Cutout 82mm
- LED Driver Remote
- Trimless version No

### Electronic control gear

NON-DIM/Dimmable


**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.



⊕ Cutout: 82mm

⊕ 5-25mm

Light Distribution For 2700K  
medium 34.7°

h(m)	E(lx)	ø(m)
1	2983	ø0.62
2	745.7	ø1.25
3	331.4	ø1.87
4	186.4	ø2.50
5	119.3	ø3.12

**\*\*The specification is subject to change without notes.\*\***