




SHOWER/SPOT LIGHT/FIXED/IP65/LINEAR

Model: SR-DL3179



 Cutout: 152x42mm

 5-25mm

Feature:

- Compact recessed downlight
- Linear shower spot
- Available with honeycomb louver

Technical data:


| | |
|--------------------------|------------------------------------|
| ▪ Light source | High power LED or other |
| ▪ LED Power (max) | 10.5W (700mA, 15V) |
| ▪ System Power (ref.) | 15W (ref. only depends on the ECG) |
| ▪ Lumen flux (typ.) | 800lm (without honeycomb) |
| ▪ | 500lm (with honeycomb) |
| ▪ Colour temperature | 2700K, 3000K, 4000K |
| ▪ Colour rendering index | Ra \geq 90 |
| ▪ MacAdam Step | 3 |
| ▪ Beam Angle | 15D, 24D, 36D Reflector |
| ▪ Tiltable | No |
| ▪ Ingress protection | IP65 |
| ▪ Operation temperature | 0-40C |
| ▪ Protection Class | III |
| ▪ LED Life time | 50,000h L70B10 |
| ▪ Finishing | Nature Stainless Steel |
| ▪ Construction | Aluminum |
| ▪ Installation | Ceiling Recessed, spring type |
| ▪ Dimension | 160x49mmx46mm(H)/Cutout 152x42mm |
| ▪ LED Driver | Remote |
| ▪ Trimless version | No |

Electronic control gear

NON-DIM/Dimmable

 MP series

1-10V/0-10V/DALI

 SC series

Other brand is available upon request

*Use IDP multi-power LED Driver can trim down the output power according to actual application.

****The specification is subject to change without note.****