


## SURFACE/SPOT LIGHT/FIXED

**Model: SU-SD3016**



### Feature:

- Surface mount spot light
- IP54
- Fixed version

### Technical data:

- Light source COB or others
- LED Power (max) 7.2W (200mA, 36V)
- System Power (ref.) 9W (ref. only depends on the ECG)
- Lumen flux (typ.) 600lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index  $Ra \geq 90$
- MacAdam Step 3
- Beam Angle 24D, 36D 45D PMMA lens
- Tiltable No
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Surface mount
- Dimension 97mm(OD)x128mm(H)
- LED Driver Build i
- Trimless version no

### Electronic control gear

Build in on/off LED driver  
(Dimmable LED Driver is on request)

#### Light Distribution For 3000K

medium 36°			wide 47°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	1218	ø0.65	1	1399	ø0.86
2	304.6	ø1.30	2	349.7	ø1.73
3	135.4	ø1.95	3	155.4	ø2.60
4	76.15	ø2.60	4	78.44	ø3.47
5	48.74	ø3.25	5	55.96	ø4.34

**\*\*The specification is subject to change without note.\*\***