

## TRACK/DOME GLASS SHIELD/ANTI-GLARE

**Model: TRA-TR3040**



### Feature:

- Dome shape glass shield
- 220Vac or 48Vdc track available
- Build in track LED driver

### Technical data:

- |                          |   |
|--------------------------|---|
| ▪ Light source           | COB or others                                     |
| ▪ LED Power (max)        | 12.6W (350mA, 36V)                                |
| ▪ System Power (ref.)    | 15W <small>(ref. only depends on the ECG)</small> |
| ▪ Lumen flux (typ.)      | 900lm   |
| ▪ Colour temperature     | 2700K, 3000K, 4000K                               |
| ▪ Colour rendering index | Ra $\geq$ 90                                      |
| ▪ MacAdam Step           | 3   |
| ▪ Beam Angle             | 24D, 36D, 60D Reflector                           |
| ▪ Tiltable               | No  |
| ▪ Ingress protection     | IP21  |
| ▪ Operation temperature  | 0-40C   |
| ▪ Protection Class       | III   |
| ▪ LED Life time          | 50,000h L70B10                                    |
| ▪ Finishing              | White/Black                                       |
| ▪ Construction           | Aluminum  |
| ▪ Installation           | Track   |
| ▪ Dimension              | 100mm(OD)x330mm(H)                                |
| ▪ LED Driver             | Build in track LED Driver                         |
| ▪ Trimless               | NA  |

### Electronic control gear

Build in track On/Off LED Driver  
(Dimmable LED Driver is on request)

**\*\*The specification is subject to change without note.\*\***

